RECTANGULAR TYPE LED

Features

- High intensity
- Wide viewing angle
- General purpose leads
- Reliable and rugged

Package Dimensions



Unit: mm (inches)
Tolerance: ± 0.25mm (.010") max.

Absolute Maximum Ratings at Ta=25℃

Parameter	Max.	Unit
Power Dissipation	100	mW
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	100	mA
Continuous Forward Current	40	mA
Derating Linear From 50℃	0.4	mA / ℃
Reverse Voltage	5	V
Operating Temperature Range	-40℃ to +80℃	
Storage Temperature Range	-40℃ to +80℃	
Lead Soldering Temperature [4mm(.157") From Body]	260℃ for 5 Seconds	

Notes:

1. All dimensions are in millimeters (inches).
2. Protruded resin under flange is 1.0mm (.04") max.
3. Lead spacing is measured where the leads emerge from the package.
4. Specifications are subject to change without notice.

Part No.	Emitting Color	Lens Color	Peak Wavelength λp (nm)	Vf (V) I_f = 20mA (Note E1)		Iv (mcd) (Note E2)		Viewing Angle $2\theta_{1/2}$ (Deg) (Note E3)
				Min	Typ	Min	Typ	
EL-25RU31	Hi-Red	Red Diffused	660	1.7	2.0	15	25	100
EL-25GU31	Hi-Green	Green Diffused	570	1.7	2.2	10	15	100
EL-25YU31	Hi-Yellow	Yellow Diffused	590	1.7	2.0	18	22	100
EL-25RU32	Hi-Red	Water Clear	660	1.7	2.0	25	35	100
EL-25GU32	Hi-Green	Water Clear	570	1.7	2.2	20	25	100
EL-25YU32	Hi-Yellow	Water Clear	590	1.7	2.0	35	45	100
EL-25RU33	Hi-Red	Red Transparent	660	1.7	2.0	25	35	100
EL-25GU33	Hi-Green	Green Transparent	570	1.7	2.2	20	25	100
EL-25YU33	Hi-Yellow	Yellow Transparent	590	1.7	2.0	35	45	100

Parameter	Test Condition
Luminous Intensity	I_f = 20mA (Note E1. Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.)
Dominant Wavelength	I_f = 20mA (Note E2: The dominant wavelength (λd) is derived from the CIE chromaticity diagram and represents the single wavelength which defines the color of the device.)
Peak Emission Wavelength	I_f = 20mA
Viewing Angle	(Note E3. $\theta_{1/2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.)
Spectral Line Half-Width	I_f = 20mA
Forward Voltage	I_f = 20mA
Reverse Current	I_f = 20mA

Elite Enterprises (H.K.) Co., Ltd.
Flat 2307, 23/F., Paul Y. Centre, 51 Hung To Road, Kwun Tong, H.K.
Tel: (852) 2723-3122 Fax: (852) 2723-3990 Email: info@elite-ent.com.hk